

Formula Sheet:

Electricity and Magnetism

Coulomb's law

$$F = k \frac{qQ}{r^2}$$

Electric Field

$$\vec{E} = \frac{\vec{F}}{q}$$

Field of a point charge

$$E = k \frac{Q}{r^2}$$

Electric field inside a capacitor

$$E = \frac{\eta}{\epsilon_0}$$

Principle of superposition

$$\vec{E}_{net} = \sum_{i=1}^N \vec{E}_i$$

Electric flux

$$\Phi_E = \int \vec{E} \cdot d\vec{A}$$

Gauss's law

$$\Phi = \oint \vec{E} \cdot d\vec{A} = \frac{Q_{in}}{\epsilon_0}$$

Electric potential

$$V = \frac{U}{q}$$

$$V(r) = - \int_{\infty}^r \vec{E} \cdot d\vec{l}$$

$$V_{ba} = V_b - V_a = - \int_a^b \vec{E} \cdot d\vec{l}$$

For a point charge $V(r) = \frac{1}{4\pi\epsilon_0} \frac{Q}{r}$

For a parallel-plate capacitor

$$V = Es$$

Potential Energy

$$U = qV$$

Capacitors

$$C = \frac{Q}{\Delta V}$$

Parallel-plate $C = \epsilon_0 \frac{A}{d}$

Capacitors connected in parallel

$$C_{eq} = C_1 + C_2 + \dots$$

Capacitors connected in series

$$\frac{1}{C_{eq}} = \frac{1}{C_1} + \frac{1}{C_2} + \dots$$

Energy stored in a capacitor $U = \frac{Q^2}{2C}$

Ohm's law

$$V = IR$$

$$R = \rho \frac{l}{A}$$

Power

$$P = IV$$

Resistors connected in series

$$R_{eq} = R_1 + R_2 + R_3 + \dots$$

Resistors connected in parallel

$$\frac{1}{R_{eq}} = \frac{1}{R_1} + \frac{1}{R_2} + \frac{1}{R_3} + \dots$$

The potential difference across a charging capacitor in RC circuit

$$V(t) = \epsilon(1 - e^{-t/RC})$$

A magnetic field exerts a force

$$\vec{dF} = I \vec{dl} \times \vec{B}$$

$$\vec{F} = I \vec{l} \times \vec{B}$$

$$\vec{F} = q \vec{v} \times \vec{B}$$

The Biot-Savart Law

$$\vec{B} = \frac{\mu_0 q \vec{v} \times \hat{r}}{4\pi r^2}$$

$$d\vec{B} = \frac{\mu_0 I d\vec{s} \times \hat{r}}{4\pi r^2}$$

The magnetic field of:

A straight line wire

$$B = \frac{\mu_0 I}{2\pi r}$$

A solenoid

$$B = \mu_0 n I$$

Magnetic flux

$$\Phi_B = \int \vec{B} \cdot d\vec{A}$$

Self-inductance

$$L = N \frac{\Phi_B}{I}; \quad \varepsilon = -L \frac{dI}{dt}$$

Energy stored in an inductor

$$U = L \frac{I^2}{2}$$

“Discharged” LR circuit

$$I = I_0 e^{-t/\tau}; \quad \tau = L/R$$

Maxwell's equations

$$\oint \vec{E} \cdot d\vec{A} = \frac{Q}{\varepsilon_0}$$

$$\oint \vec{B} \cdot d\vec{A} = 0$$

$$\varepsilon = \oint \vec{E} \cdot d\vec{s} = -\frac{d\Phi_B}{dt}$$

$$\oint \vec{B} \cdot d\vec{s} = \mu_0 I + \mu_0 \varepsilon_0 \frac{d\Phi_E}{dt}$$

$$\vec{F} = q(\vec{E} + \vec{v} \times \vec{B})$$

The Poynting vector

$$\vec{S} = \frac{1}{\mu_0} (\vec{E} \times \vec{B})$$

Malus's Law

$$I = I \cos^2 \theta$$

Traveling Wave

$$y(x, t) = A \sin(kx - \omega t + \phi_0)$$

$$k = \frac{2\pi}{\lambda}; \quad \omega = \frac{2\pi}{T}; \quad v = \lambda f$$

Interference

$$\Delta\phi = 2\pi \frac{\Delta r}{\lambda} + \Delta\phi_0 = m2\pi \text{ (constr)}$$

$$\begin{aligned} \Delta\phi &= 2\pi \frac{\Delta r}{\lambda} + \Delta\phi_0 \\ &= (m + \frac{1}{2})2\pi \text{ (destr)} \end{aligned}$$

$$A = \left| 2a \cos\left(\frac{\Delta\phi}{2}\right) \right|$$

Standing Waves

$$A(x) = 2a \sin(kx)$$

$$\lambda_m = \frac{2L}{m}; \quad f_m = m \frac{v}{2L}$$

Double Slit

$$y_m = \frac{m\lambda L}{d}, \quad m=0, 1, 2$$

Diffraction grating

$$d \sin \theta_m = m\lambda$$

$$y_m = L \tan \theta_m$$

Thin-lens equation:

$$\frac{1}{f} = \frac{1}{s} + \frac{1}{s'}$$

$$m = -\frac{s'}{s}; \quad |m| = \frac{h'}{h}$$

Snell's Law:

$$n_1 \sin \theta_1 = n_2 \sin \theta_2$$

$$\text{TIR: } \sin \theta_c = \frac{n_2}{n_1}$$

Constants

Charge on electron

$$e = 1.60 \cdot 10^{-19} \text{ C}$$

Electron mass $m = 9.11 \cdot 10^{-31} \text{ kg}$

Permittivity of free space

$$\epsilon_0 = 8.85 \cdot 10^{-12} \text{ C}^2/\text{Nm}^2$$

Permeability of free space

$$\mu_0 = 4\pi \cdot 10^{-7} \text{ Tm/A}$$

$$k = \frac{1}{4\pi\epsilon_0} = 8.99 \cdot 10^9 \text{ Nm}^2/\text{C}^2$$

$$c = \frac{1}{\sqrt{\epsilon_0\mu_0}} = 3.0 \cdot 10^8 \text{ m/s}$$

Kinematic eq-ns with const. Acc.:

$$v(t) = v_{0x} + at$$

$$x(t) = x_0 + v_{0x}t + (1/2) at^2$$

$$v^2 = v_{0x}^2 + 2a(x - x_0)$$

Centripetal acceleration $a_R = v^2/r$