

Formula Sheet:

Electricity and Magnetism

Coulomb's law

$$F = k \frac{qQ}{r^2}$$

Electric Field

$$\vec{E} = \frac{\vec{F}}{q}$$

Field of a point charge

$$E = k \frac{Q}{r^2}$$

Electric field inside a capacitor

$$E = \frac{\eta}{\epsilon_0}$$

Principle of superposition

$$\vec{E}_{net} = \sum_{i=1}^N \vec{E}_i$$

Electric flux

$$\Phi_E = \int \vec{E} \cdot d\vec{A}$$

Gauss's law

$$\Phi = \oint \vec{E} \cdot d\vec{A} = \frac{Q_{in}}{\epsilon_0}$$

Electric potential

$$V = \frac{U}{q}$$

$$\Delta V = V_f - V_i = - \int_i^f \vec{E} \cdot d\vec{s}$$

For a point charge $V(r) = \frac{1}{4\pi\epsilon_0} \frac{Q}{r}$

For a parallel-plate capacitor

$$V = Es$$

Potential Energy

$$U = qV$$

Two point charges

$$U = k \frac{qQ}{r}$$

Capacitors

$$C = \frac{Q}{\Delta V}$$

Parallel-plate $C = \epsilon_0 \frac{A}{d}$

Capacitors connected in parallel

$$C_{eq} = C_1 + C_2 + \dots$$

Capacitors connected in series

$$\frac{1}{C_{eq}} = \frac{1}{C_1} + \frac{1}{C_2} + \dots$$

Energy stored in a capacitor $U = \frac{Q^2}{2C}$

Ohm's law

$$V = IR$$

$$I = \frac{dQ}{dt}$$

$$R = \rho \frac{l}{A}$$

$$\sum I_{in} = \sum I_{out}$$
$$\sum \Delta V_i = 0$$

Power

$$P = IV$$

Resistors connected in series

$$R_{eq} = R_1 + R_2 + R_3 + \dots$$

Resistors connected in parallel

$$\frac{1}{R_{eq}} = \frac{1}{R_1} + \frac{1}{R_2} + \frac{1}{R_3} + \dots$$

The potential difference across a charging capacitor in RC circuit

$$V(t) = \varepsilon(1 - e^{-t/RC})$$

A magnetic field exerts a force

$$\vec{dF} = I\vec{dl} \times \vec{B}$$

$$\vec{F} = I\vec{l} \times \vec{B}$$

$$\vec{F} = q\vec{v} \times \vec{B}$$

The Biot-Savart Law

$$\vec{B} = \frac{\mu_0 q \vec{v} \times \hat{r}}{4\pi r^2}$$

$$d\vec{B} = \frac{\mu_0 I d\vec{s} \times \hat{r}}{4\pi r^2}$$

The magnetic field of:

A straight line wire

$$B = \frac{\mu_0 I}{2\pi r}$$

A solenoid

$$B = \mu_0 n I$$

Magnetic flux

$$\Phi_B = \int \vec{B} \cdot d\vec{A}$$

Inductance

$$L = \frac{\Phi_B}{I}$$

$$L = \frac{\mu_0 N^2 A}{l}$$

$$\varepsilon = -L \frac{dI}{dt}$$

Energy stored in an inductor

$$U = L \frac{I^2}{2}$$

“Discharged” LR circuit

$$I = I_0 e^{-t/\tau}; \tau = L/R$$

Faraday’s Law

$$\varepsilon = \oint \vec{E} \cdot \vec{ds} = - \frac{d\Phi_B}{dt}$$

Ampere’s Law

$$\oint \vec{B} \cdot \vec{ds} = \mu_0 I$$

$$r_{cyc} = \frac{mv}{qB}$$

Constants

Charge of an electron

$$e = 1.60 \cdot 10^{-19} C$$

Electron mass $m = 9.11 \cdot 10^{-31} kg$

Permittivity of free space

$$\varepsilon_0 = 8.85 \cdot 10^{-12} C^2/Nm^2$$

Permeability of free space

$$\mu_0 = 4\pi \cdot 10^{-7} Tm/A$$

$$k = \frac{1}{4\pi\varepsilon_0} = 8.99 \cdot 10^9 Nm^2/C^2$$

Kinematic eq-ns with const. Acc.:

$$v(t) = v_{0x} + at$$

$$x(t) = x_0 + v_{0x}t + (1/2) at^2$$

$$v^2 = v_{0x}^2 + 2a(x - x_0)$$

Centripetal acceleration $a_R = v^2/r$

$$L = 2\pi R$$

$$A = \pi R^2$$

$$V = (4/3)\pi R^3$$